



## Titanium Series T5 HO 24W DIR

For models: 24T5HO/4F/xxx/DIR Where xxx means 818-965 which indicates CRI and color temperature

## **Electronic Ballast Compatibility**

| Series                 | Model                             | Туре | Compatibility |
|------------------------|-----------------------------------|------|---------------|
| Philips - Advance      | ICN-2S54-T                        | PS   | OK            |
| Philips - Advance      | ICN-4S54-90C-2LS-G                | PS   | OK            |
| GE - Ultrastart        | GE54MVPS90-E-S                    | PS   | OK            |
| GE - Ultrastart        | GE454MVPS90-E-S                   | PS   | OK            |
| GE - Ultrastart        | GE454MVPS90-F                     | PS   | OK            |
| Universal - Triad      | B254PUNVHB-D                      | PS   | OK            |
| Universal - Triad      | B454PUNVHB-E                      | PS   | OK            |
| Universal - Triad      | B454PUNV-E                        | PS   | OK            |
| Plusrite               | BAF454PS/MV                       | PS   | OK            |
| Howard                 | EP2/54HO/PRS/MV/W/MC              | PS   | OK            |
| Sylvania - Quicktronic | QHE 2X54T5HO/UNV PSN HT           | PS   | OK            |
| Sylvania - Quicktronic | QHE 4X54T5HO/UNV PSN HT SCL [DOE] | PS   | OK            |
| Fulham                 | RHA-UNV-254-LT5                   | PS   | OK            |
| Fulham                 | RHA-UNV-454-LT5                   | PS   | OK            |
| Watran                 | DB-254HO-MV-TP-PS-SL              | PS   | OK            |
| Sunpark                | U-154T5HO-1                       | IS   | OK            |
| Sunpark                | U-254T5HO-1                       | IS   | OK            |

\*GREEN CREATIVE has provided this ballast compatibility chart for guidance when selecting a ballast and lamp combination. Lamps were tested for compatibility with the above listed Instant Start (IS) and Programmed Start (PS) ballasts. Ballasts that do not appear on the chart might still be compatible but have not been tested. All testing has been performed with a stable main supply. The quality of the local main, existing installation and wiring, as well as different manufacturer versions of the above ballasts may affect lamp performance. Since no assurance can be provided regarding these factors, it is a general recommendation to perform a test on-site prior to installing the LED lamps.