



GE
Lighting

68838 - F54T5/XL/841/ECO

F54T5/XL/841/ECO

GENERAL CHARACTERISTICS

| | |
|---------------------------------|---------------------------------|
| Base Description | Miniature Bi-Pin |
| Base Type | Pin/Plug-In |
| Mercury Content | 2.5 mg |
| Mercury-Picogram per mean lm hr | 10.9 |
| Rated Life Rapid Start - Hrs | 50000 h @ 3 h 60000 h @ 12 h |
| Starting Temp (MIN) C-degrees | -20 °C |
| Bulb Material | Sodalime glass |
| Rated Life Hours-nominal | 60000 h |
| Primary Application | Garage & Basement |
| Product Technology | Linear Fluorescent |
| Base | G5 |
| Bulb Shape | T5 |

PHOTOMETRIC CHARACTERISTICS

| | |
|--------------------------------|---------|
| Mean Lumens nominal | 4600 lm |
| Nominal Initial Lumen per Watt | 93 |
| Initial Lumens-nominal | 5000 lm |
| Color Rendering Index-CRI | 84 |
| Color Temperature | 4100 K |

PRODUCT INFORMATION

| | |
|----------------------------------|------------------|
| Product Code | 68838 |
| Description | F54T5/XL/841/ECO |
| Alternative Unit Of Measure | 00-Case |
| Standard Package Quantity | 40 |
| Ean UPC | 043168688383 |
| Standard Package GTIN | 10043168688380 |
| No Of Items Per Sales Unit | 1 |
| No Of Items Per Standard Package | 40 |
| Sales Unit | Unit |
| UCC | 043168688383 |

DIMENSIONS

| | |
|----------------|----------|
| Diameter | 0.625 in |
| Nominal Length | 45.2 in |

ELECTRICAL CHARACTERISTICS

| | |
|---------------------|------|
| Rated power (Watts) | 54 W |
|---------------------|------|