

GE
Lighting

awaken



LED replacement lamps



ecomaginationSM



imagination at work

exceeding expectations

Why choose GE'S LED Lamps?

Innovation leadership

A GE scientist invented the first visible LED in 1962, pioneering a technology that is revolutionizing the lighting industry. That was our start and now we are dedicated to constantly improving LED performance. We continually invest in new products and the latest upgrades to make sure our best LED solutions are available.



Trust

We've been here. We'll be here. Built into each of GE's LED replacement lamps is 125 years of experience, reliability and innovation. Every performance claim we make is supported by stringent, comprehensive testing—ensuring that your lighting investment pays off today and in the future.

Long life

GE's LED replacement lamps are sturdy, dependable and long lasting. Depending on the lamp, you can expect up to 50,000 hours of rated life. That's 12 hours a day, every day of the year, for over a decade.

Short payback period

Decreased energy and maintenance costs, combined with utility rebates, deliver results that often exceed your expectations.





Family of solutions

Directional. Omni-directional. Decorative. Dimming. Tight optical control. Accent. Task. Display. Indoor. Outdoor. You name it. We've got it in LED.








LED replacement lamps

Decorative Lamps

| Bulb Shape | Base Type | Watts | Order Code | Description | Volts | Case Qty** | MOL (In) | Lumens Initial | CBCP | Initial Color Temp | CRI | Wattage Replacement | *Rated Life L70 (Hrs) | Dimmable | ENERGY STAR® Status | #Location Rating | Additional Information | | |
|--|------------------|------------------|------------|--|------------------|------------------|----------|----------------|------|--------------------|------|---------------------|-----------------------|----------|---------------------|------------------|------------------------|-----------------|-----------------|
| Candles | | | | | | | | | | | | | | | | | | | |
|  | CA11 | MED | 3.5 | 68168 | LED3DCAM-C/TP | 120 | 3 | 4.2 | 170 | | 2700 | 80 | 25W | 15,000 | Yes | ★ | Damp | Clear, Bent tip | |
| | | | | 68167 | LED4DCAM-F/TP | 120 | 3 | 4.2 | 270 | | 2700 | 82 | 25W | 15,000 | Yes | ★ | Damp | Frost, Bent tip | |
| | | | | 65655 | LED4DCAM-C/827 | 120 | 3 | 4.2 | 300 | | 2700 | 80 | 40W | 15,000 | Yes | ★ | Damp | Clear, Bent tip | |
| | | | | 23707 | LED4DCAM-C/5K/TP | 120 | 3 | 4.2 | 350 | | 5000 | 80 | 40W | 15,000 | Yes | ★ | Damp | Clear, Bent tip | |
| | | | | 21250 | LED4DCAM-C3/827 | 120 | 6 | 4.2 | 300 | | 2700 | 80 | 40W | 15,000 | Yes | ★ | Damp | Clear, Bent tip | |
| | | | | 75554 | LED4DCAMCF/824 | 120 | 6 | 4.2 | 250 | | 2400 | 80 | 25W | 15,000 | Yes | ★ | Damp | Clear, Bent tip | |
| | | | | 4.5 | 23706 | LED4.5DCAM-F5KTP | 120 | 3 | 4.2 | 350 | | 5000 | 80 | 40W | 15,000 | Yes | ★ | Damp | Frost, Bent tip |
| | | | | | 89950 | LED4.5DCAM-F/TP | 120 | 3 | 4.2 | 300 | | 2700 | 80 | 40W | 15,000 | Yes | ★ | Damp | Frost, Bent tip |
| | | | | | 21251 | LED7DCAM-C3/827 | 120 | 6 | 4.8 | 500 | | 2700 | 80 | 60W | 15,000 | Yes | ★ | Damp | Clear, Bent tip |
| | | | |  | CAND | 3.5 | 68166 | LED3DCAC-C/TP | 120 | 3 | 4.3 | 170 | | 2700 | 80 | 25W | 15,000 | Yes | ★ |
| 68165 | LED4DCAC-F/TP | 120 | 3 | | | | 4.3 | 270 | | 2700 | 82 | 25W | 15,000 | Yes | ★ | Damp | Frost, Bent tip | | |
| 65654 | LED4DCAC-C/827 | 120 | 3 | | | | 4.2 | 300 | | 2700 | 80 | 40W | 15,000 | Yes | ★ | Damp | Clear, Bent tip | | |
| 23691 | LED4DCAC-C/5K/TP | 120 | 3 | | | | 4.2 | 350 | | 5000 | 80 | 40W | 15,000 | Yes | ★ | Damp | Frost, Bent tip | | |
| 21231 | LED4DCAC-C3/827 | 120 | 6 | | | | 4.3 | 300 | | 2700 | 80 | 40W | 15,000 | Yes | ★ | Damp | Clear, Bent tip | | |
| 75553 | LED4DCACCF/824 | 120 | 6 | | | | 4.3 | 250 | | 2400 | 80 | 25W | 15,000 | Yes | ★ | Damp | Clear, Bent tip | | |
| 4.5 | 89948 | LED4.5DCAC-F/TP | 120 | | | | 3 | 4.2 | 300 | | 2700 | 80 | 40W | 15,000 | Yes | ★ | Damp | Frost, Bent tip | |
| | 22239 | LED4.5DCAC-F5KTP | 120 | | | | 3 | 4.2 | 350 | | 5000 | 80 | 40W | 15,000 | Yes | ★ | Damp | Frost, Bent tip | |
| | 21233 | LED7DCAC-C3/827 | 120 | | | | 6 | 4.8 | 500 | | 2700 | 80 | 60W | 15,000 | Yes | ★ | Damp | Clear, Bent tip | |
| Globes | | | | | | | | | | | | | | | | | | | |
|  | G16.5 | CAND | 4.5 | 68169 | LED4DG16C-W/TP | 120 | 3 | 3.0 | 270 | | 2700 | 82 | 25W | 15,000 | Yes | ★ | Damp | White | |
| | | | | 68170 | LED4DG16C-C/TP | 120 | 3 | 3.0 | 270 | | 2700 | 82 | 25W | 15,000 | Yes | ★ | Damp | Clear | |
| | | | | 89952 | LED5DG16C-W/TP | 120 | 3 | 3.0 | 350 | | 2700 | 80 | 40W | 15,000 | Yes | ★ | Damp | White | |
|  | G25 | MED | 4.5 | 68171 | LED4DG25M-W/TP | 120 | 3 | 4.3 | 280 | | 2700 | 82 | 25W | 15,000 | Yes | ★ | Damp | White | |
| | | | | 68172 | LED4DG25M-C/TP | 120 | 3 | 4.3 | 280 | | 2700 | 82 | 25W | 15,000 | Yes | ★ | Damp | Clear | |
| | | | | 64678 | LED5DG25M-W/827 | 120 | 6 | 4.3 | 350 | | 2700 | 80 | 40W | 15,000 | Yes | ★ | Damp | White | |
| | | | | 21253 | LED5DG25-W3/827 | 120 | 6 | 4.3 | 350 | | 2700 | 80 | 40W | 15,000 | Yes | ★ | Damp | White | |
| | | | | 7 | 21255 | LED7DG25-W3/827 | 120 | 6 | 4.3 | 500 | | 2700 | 80 | 60W | 15,000 | Yes | ★ | Damp | White |

A-Line Lamps

| Bulb Shape | Base Type | Watts | Order Code | Description | Volts | Case Qty** | MOL (In) | Lumens Initial | CBCP | Initial Color Temp | CRI | Wattage Replacement | *Rated Life L70 (Hrs) | Dimmable | ENERGY STAR® Status | #Location Rating | Additional Information | |
|--|------------------|-------|--|------------------|------------------|------------|---------------|----------------|------|--------------------|------|---------------------|-----------------------|----------|---------------------|------------------|-------------------------|------------------------|
| A-15 | | | | | | | | | | | | | | | | | | |
|  | MED | 4.5 | 68173 | LED4DA15-W/TP | 120 | 3 | 3.5 | 270 | | 2700 | 82 | 25W | 15,000 | Yes | | Damp | White | |
| | | | 68174 | LED4DA15-C/TP | 120 | 3 | 3.5 | 270 | | 2700 | 82 | 25W | 15,000 | Yes | | Damp | Clear | |
| | | | 14644 | LED4.5DA15-C/827 | 120 | 6 | 3.5 | 300 | | 2700 | 80 | 40W | 15,000 | Yes | | Damp | Clear | |
| | | | 23708 | LED4.5DA15-W5KTP | 120 | 3 | 3.5 | 350 | | 5000 | 80 | 40W | 15,000 | Yes | | Damp | White | |
| | | | 23724 | LED4.5DA15-C5KTP | 120 | 3 | 3.5 | 350 | | 5000 | 80 | 40W | 15,000 | Yes | | Damp | Clear | |
| | | | 83645 | LED4.5DA15C-FRIG | 120 | 3 | 3.5 | 350 | | 5000 | 80 | 40W | 15,000 | Yes | | Damp | Clear Refrigerator bulb | |
| A-19 | | | | | | | | | | | | | | | | | | |
|  | MED | 7 | 14063 | LED7DAV3/827W | 120 | 6 | 4.6 | 470 | | 2700 | 80 | 40W | 25,000 | Yes | | Damp | White, Semi-Omni | |
| | | | 95928 | LED7DAV3/5K | 120 | 6 | 4.6 | 500 | | 5000 | 80 | 40W | 25,000 | Yes | | Damp | White, Semi-Omni | |
| | | | 11332 | LED7DA19/827 | 120 | 6 | 4.4 | 450 | | 2700 | 80 | 40W | 25,000 | Yes | ★ | Damp | White, Omnidirectional | |
| | | | 71208 | LED7DA19/830 | 120 | 6 | 4.4 | 450 | | 3000 | 80 | 40W | 25,000 | Yes | ★ | Damp | White, Omnidirectional | |
| | | | 34238 | LED7DA19/824 | 120 | 6 | 4.44 | 450 | | 2400 | 80 | 40W | 25,000 | Yes | | Damp | White | |
| | | | 92140 | LED7A19BUG | 120 | 3 | 4.63 | 400 | | | | 40W | 15,000 | - | | Damp | Bug Light | |
| | | | 10.5 | 13791 | LED11DAV3/827W | 120 | 6 | 4.6 | 800 | | 2700 | 80 | 60W | 15,000 | Yes | | Damp | White, Semi-Omni |
| | | | | 95927 | LED11DAV3/5K | 120 | 6 | 4.4 | 850 | | 5000 | 80 | 60W | 15,000 | Yes | | Damp | White, Semi-Omni |
| | | | | 11328 | LED11DA19/827 | 120 | 6 | 4.4 | 800 | | 2700 | 80 | 60W | 25,000 | Yes | ★ | Damp | White, Omnidirectional |
| | | |  | 11 | 11 | 71209 | LED11DA19/830 | 120 | 6 | 4.4 | 800 | | 3000 | 80 | 60W | 25,000 | Yes | ★ |
| 29268 | LED11DA19/824 | 120 | | | | 6 | 4.44 | 800 | | 2400 | 80 | 60W | 25,000 | - | | Damp | White, Omnidirectional | |
| 74357 | LED11DA19827GU24 | 120 | | | | 6 | 5.43 | 800 | | 2700 | 80 | 60W | 25,000 | - | ★ | Damp | White, Omnidirectional | |
| A-Line reveal® | | | | | | | | | | | | | | | | | | |
|  | MED | 7 | 63178 | LED7DA19RVLESTP | 120 | 3 | 4.43 | 450 | | 2700 | 84 | 40w | 25,000 | Yes | | Damp | White, Omnidirectional | |
| | | | 11 | 63180 | LED11DA19RVLESTP | 120 | 3 | 4.43 | 800 | | 2700 | 84 | 60w | 25,000 | Yes | | Damp | White, Omnidirectional |
| | | | 14 | 92284 | LED14DA21RVL/TP | 120 | 3 | 5.28 | 1100 | | 2700 | 85 | 75w | 25,000 | Yes | | Damp | White, Omnidirectional |
| A-21 | | | | | | | | | | | | | | | | | | |
|  | MED | 12 | 73384 | LED12A21/830FE | 120 | 6 | 5.31 | 1100 | | 3000 | 80 | 100W | 25,000 | Yes | | Damp | White, Enclosed, Omni | |
| | | | 73404 | LED12DA21/850FE | 120 | 6 | 5.31 | 1100 | | 5000 | 80 | 100W | 25,000 | Yes | | Damp | White, Enclosed, Omni | |
| | | | 13 | 12422 | LED13DA212/827 | 120 | 6 | 5.28 | 1100 | | 2700 | 80 | 75W | 25,000 | Yes | ★ | Damp | White, Omnidirectional |
| | | | 14 | 94936 | LED14DA21/827W | 120 | 6 | 5.3 | 1100 | | 2700 | 80 | 75W | 15,000 | Yes | | Damp | White, Semi-Omni |
| | | | 16 | 12349 | LED16DA212/827 | 120 | 6 | 5.28 | 1600 | | 2700 | 80 | 100W | 25,000 | Yes | ★ | Damp | White, Omnidirectional |
| | | | 12399 | LED16DA212/830 | 120 | 6 | 5.3 | 1600 | | 3000 | 80 | 100W | 25,000 | Yes | ★ | Damp | White, Omnidirectional | |
| | GU24 | | 92498 | LED16DA21827GU24 | 120 | 6 | 5.43 | 1600 | | 2700 | 80 | 100W | 25,000 | Yes | ★ | Damp | White | |

Information provided is subject to change without notice. Please verify all details with GE. All values are design or typical values when measured under laboratory conditions, and GE makes no warranty or guarantee, expressed or implied, that such performance will be obtained under end-use conditions.

* The life rating is based on the hours of operation the lamp will provide before reaching 70% of its original rating (L70)

** Minimum order quantity = 6

★ ENERGY STAR® status: ENERGY STAR® certified. Lamps without a ★ are not ENERGY STAR® certified.

UL 1993 Environmental Requirements for LED LAMPS

Location, damp - Exterior or interior location that is normally or periodically subject to condensation of moisture in, on, or adjacent to, electrical equipment, and includes partially protected locations.

Location, dry - Location not normally subject to dampness, may include a location subject to temporary dampness, i.e., building under construction, provided ventilation is adequate to prevent an accumulation of moisture.

Location, wet - Location in which water or other liquid can drip, splash, or flow on or against electrical equipment.


Notes: 1) Product descriptions ending in "/TP" indicate a carded blister or clamshell package nested in a tray for shelf display. Cards also designed for hook display.

2) LED A19 Locking device works on PC: 85791, 85792, 89898, 62182, 89899 and 89900


Get more information at
GELighting.com/ThinkLED

LED replacement lamps


A-Line Lamps (Continued)

| Bulb Shape | Base Type | Watts | Order Code | Description | Volts | Case Qty** | MOL (In) | Lumens Initial | CBCP | Initial Color Temp | CRI | Wattage Replacement | *Rated Life L70 (Hrs) | Dimmable | ENERGY STAR® Status | #Location Rating | Additional Information |
|--|-----------|-------|------------|------------------|-------|------------|----------|----------------|------|--------------------|-----|---------------------|-----------------------|----------|---------------------|------------------|------------------------|
|  | MED | 16 | 73376 | LED16A30/100/827 | 120 | 6 | 5.31 | 400/1600/1050 | | 2700 | 80 | 30/70/100 | 25,000 | - | ★ | Damp | 3-Way |
| | | | 92118 | LED16A30/100/5KB | 120 | 3 | 5.31 | 400/1600/1050 | | 5000 | 80 | 30/70/100 | 25,000 | - | | | |
| | MED | 17 | 16113 | LED17DA21/827 | 120 | 6 | 5.3 | 1600 | | 2700 | 78 | 100W | 15,000 | Yes | | Damp | White, Semi-Omni |
| | | | 73378 | LED22A50/150/827 | 150 | 6 | 5.31 | 700/2155/1600 | | 2700 | 80 | 50/100/150 | 25,000 | - | | Damp | 3-Way |
| | | | 92120 | LED22A50/150/5KB | 120 | 3 | 5.31 | 700/2155/1600 | | 5000 | 80 | 50/100/150 | 25,000 | - | | | White, 3-Way |




LED Bright Stik™

| Bulb Shape | Base Type | Watts | Order Code | Description | Volts | Case Qty** | MOL (In) | Lumens Initial | CBCP | Initial Color Temp | CRI | Wattage Replacement | *Rated Life L70 (Hrs) | Dimmable | ENERGY STAR® Status | #Location Rating | Additional Information |
|--|-----------|-------|------------|--------------|-------|------------|----------|----------------|------|--------------------|-----|---------------------|-----------------------|----------|---------------------|------------------|------------------------|
|  | MED | 10 | 28089 | LED10LS3/828 | 120 | 48 | 4.45 | 760 | | 2840 | 80 | 60W | 15,000 | - | | Indoor | Case = 16 3-packs |
| | | | 32273 | LED10LS3/850 | 120 | 48 | 4.45 | 760 | | 5000 | 80 | 60W | 15,000 | - | | Indoor | Case = 16 3-packs |

Reflector Lamps

| Bulb Shape | Base Type | Watts | Order Code | Description | Volts | Case Qty** | MOL (In) | Lumens Initial | CBCP | Initial Color Temp | CRI | Wattage Replacement | *Rated Life L70 (Hrs) | Dimmable | ENERGY STAR® Status | #Location Rating | Additional Information |
|---|-----------|-------|------------|------------------|-------|------------|----------|----------------|------|--------------------|-----|---------------------|-----------------------|----------|---------------------|------------------|------------------------|
|  | MED | 7 | 13829 | LED7DRS20F827 | 120 | 6 | 3.6 | 470 | | 2700 | 80 | | 25,000 | Yes | | Damp | White |
| | | | 14065 | LED7DRS20F830 | 120 | 6 | 3.6 | 470 | | 3000 | 80 | | 25,000 | Yes | | Damp | White |
|  | MED | 10 | 68160 | LED10DR303/827W | 120 | 6 | 5.4 | 700 | | 2700 | 80 | 65W | 25,000 | Yes | ★ | Damp | Frosted, White body |
| | | | 68161 | LED10DR303/830W | 120 | 6 | 5.4 | 700 | | 3000 | 80 | 65W | 25,000 | Yes | ★ | Damp | Frosted, White body |
| | | | 89942 | LED10DR303/5K/TP | 120 | 3 | 5.37 | 700 | | 5000 | 80 | 65W | 25,000 | Yes | ★ | Damp | Frosted, White body |
|  | MED | 10 | 92470 | LED10DR303RVL | 120 | 3 | 5.37 | 650 | | 2700 | 90 | 65W | 25,000 | Yes | ★ | Damp | Frosted, White body |
| | | | | | | | | | | | | | | | | | |
|  | MED | 13 | 64176 | LED13DBR40/827 | 120 | 6 | 6.3 | 1070 | | 2700 | 80 | 85W | 25,000 | Yes | ★ | Damp | Frosted, White body |
| | | | 14708 | LED13DBR40/830 | 120 | 6 | 6.3 | 1070 | | 3000 | 80 | 85W | 25,000 | Yes | ★ | Damp | Frosted, White body |
| | | | 20445 | LED13BR40/5K/TP | 120 | 3 | 6.34 | 1070 | | 5000 | 80 | 85W | 25,000 | Yes | ★ | Damp | Frosted, White body |

Directional Lamps (MR16 - GU10)

| Bulb Shape | Base Type | Watts | Order Code | Description | Volts | Case Qty** | MOL (In) | Lumens Initial | CBCP | Initial Color Temp | CRI | Wattage Replacement | *Rated Life L70 (Hrs) | Dimmable | ENERGY STAR® Status | #Location Rating | Additional Information | |
|--|------------------|-------|------------|------------------|-------------------|------------|------------------|----------------|------|--------------------|------|---------------------|-----------------------|----------|---------------------|------------------|--------------------------|-------------------------|
| 12 Volt AC/DC MR16 | | | | | | | | | | | | | | | | | | |
|  | GU5.3 | 7 | 93412 | LED7DMR16S830/15 | 12 | 6 | 2.3 | 460 | 3800 | 3000 | 80 | 35W | 25,000 | Yes | ★ | Dry | Accent, 15° beam, Silver | |
| | | | 69920 | LED7DMR16D830/25 | 12 | 6 | 1.9 | 390 | 1900 | 3000 | 83 | 35W | 25,000 | Yes | ★ | Dry | Accent, 25° beam, Silver | |
| | | | 69925 | LED7DMR16D840/15 | 12 | 6 | 1.9 | 430 | 4000 | 4000 | 87 | 35W | 25,000 | Yes | ★ | Dry | Accent, 15° beam, Silver | |
| | | | 93431 | LED7DMR16S827/15 | 12 | 6 | 1.97 | 440 | 3700 | 2700 | 80 | 35W | 25,000 | Yes | ★ | Dry | Accent, 15° beam, Silver | |
| | | | 39351 | LED7DMRX16830/35 | 12 | 6 | 1.97 | 420 | 1100 | 3000 | 82 | 35W | 25,000 | Yes | ★ | Dry | Accent, 35° beam, White | |
| | | | 69949 | LED7XDMR16S83025 | 12 | 6 | 1.9 | 500 | 2500 | 3000 | 82 | 50W | 25,000 | Yes | ★ | Dry | Accent, 25° beam, Silver | |
| | | | 69950 | LED7XDMR16S83035 | 12 | 6 | 1.9 | 500 | 1500 | 3000 | 82 | 50W | 25,000 | Yes | ★ | Dry | Accent, 35° beam, Silver | |
| | | | 69951 | LED7XDMR16S82725 | 12 | 6 | 1.9 | 480 | 2400 | 2700 | 80 | 50W | 25,000 | Yes | ★ | Dry | Accent, 25° beam, Silver | |
| | | | 69952 | LED7XDMR16S82735 | 12 | 6 | 1.9 | 480 | 1400 | 2700 | 80 | 50W | 25,000 | Yes | ★ | Dry | Accent, 35° beam, Silver | |
| | | | MRX16 | GU5.3 | 7 | 39360 | LED7DMRX16827/25 | 12 | 6 | 2.2 | 400 | 1800 | 2700 | 80 | 35W | 25,000 | Yes | ★ |
| 39405 | LED7DMRX16827/35 | 12 | | | | 6 | 2.2 | 400 | 1000 | 2700 | 80 | 35W | 25,000 | Yes | ★ | Dry | Accent, 35° beam, White | |
| 39408 | LED7DMRX16840/25 | 12 | | | | 6 | 2.2 | 460 | 2100 | 4000 | 83 | 35W | 25,000 | Yes | ★ | Dry | Accent, 25° beam, White | |
| 39427 | LED7DMRX16840/35 | 12 | | | | 6 | 2.2 | 460 | 1200 | 4000 | 83 | 35W | 25,000 | Yes | ★ | Dry | Accent, 35° beam, White | |
| | | | 21359 | LED7MRX16R930/10 | 12 | 6 | 2.01 | 350 | 8000 | 3000 | 95 | 50W | 25,000 | - | | Dry | Spot, 10° beam, Reveal | |
| Value 12 Volt AC/DC MR16 | | | | | | | | | | | | | | | | | | |
|  | GU5.3 | 6 | 39468 | LED6DMR16-V82735 | 12 | 6 | 1.8 | 430 | 1150 | 2700 | 80 | 35W | 25,000 | Yes | | Dry | Accent, 35° beam, White | |
| | | | 39438 | LED6DMR16-V83035 | 12 | 6 | 1.8 | 460 | 1200 | 3000 | 80 | 35W | 25,000 | Yes | | Dry | Accent, 35° beam, White | |
| | | | 39472 | LED6DMR16-V84035 | 12 | 6 | 1.8 | 500 | 1300 | 4000 | 80 | 35W | 25,000 | Yes | | Dry | Accent, 35° beam, White | |
| | | | 7 | 39473 | LED7XDMR16-V8325 | 12 | 6 | 1.88 | 550 | 2400 | 3000 | 80 | 50W | 25,000 | Yes | | Dry | Accent, 25° beam, White |
| | | | | 39483 | LED7XDMR16-V8335 | 12 | 6 | 1.88 | 550 | 1400 | 3000 | 80 | 50W | 25,000 | Yes | | Dry | Accent, 35° beam, White |
| | | | | 39542 | LED7XDMR16-V2725 | 12 | 6 | 1.88 | 530 | 2400 | 2700 | 80 | 50W | 25,000 | Yes | | Dry | Accent, 25° beam, White |
| | | | | 39567 | LED7XDMR16-V2735 | 12 | 6 | 1.88 | 530 | 1400 | 2700 | 80 | 50W | 25,000 | Yes | | Dry | Accent, 35° beam, White |
| 120 Volt GU10 | | | | | | | | | | | | | | | | | | |
|  | MR16 | GU10 | 4 | 89020 | LED4D/GU10/NFLTP | 120 | 3 | 2.3 | 250 | 720 | 3000 | 80 | 35W | 25,000 | Yes | ★ | Dry | Accent, 35° beam, White |
| | | | 6 | 26346 | LED6D/GU10/NFL/TP | 120 | 3 | 2.3 | 380 | 1100 | 3000 | 80 | 50W | 25,000 | Yes | ★ | Dry | Accent, 35° beam, White |

Information provided is subject to change without notice. Please verify all details with GE. All values are design or typical values when measured under laboratory conditions, and GE makes no warranty or guarantee, expressed or implied, that such performance will be obtained under end-use conditions.

* The life rating is based on the hours of operation the lamp will provide before reaching 70% of its original rating (L70)

** Minimum order quantity = 6

★ ENERGY STAR® status: ENERGY STAR® certified. Lamps without a ★ are not ENERGY STAR® certified.

UL 1993 Environmental Requirements for LED LAMPs

Location, damp - Exterior or interior location that is normally or periodically subject to condensation of moisture in, on, or adjacent to, electrical equipment, and includes partially protected locations.

Location, dry - Location not normally subject to dampness, may include a location subject to temporary dampness, i.e., building under construction, provided ventilation is adequate to prevent an accumulation of moisture.

Location, wet - Location in which water or other liquid can drip, splash, or flow on or against electrical equipment.

Notes: 1) Product descriptions ending in "/TP" indicate a carded blister or clamshell package nested in a tray for shelf display. Cards also designed for hook display. 2) LED A19 Locking device works on PC: 85791, 85792, 89898, 62182, 89899 and 89900



Get more information at
GELighting.com/ThinkLED

LED replacement lamps



Directional Lamps (PAR16 - PAR20)

| Bulb Shape | Base Type | Watts | Order Code | Description | Volts | Case Qty** | MOL (in) | Lumens Initial | CBCP | Initial Color Temp | CRI | Wattage Replacement | *Rated Life L70 (Hrs) | Dimmable | ENERGY STAR® Status | #Location Rating | Additional Information | |
|--|-----------|-------|------------|------------------|-------|------------|----------|----------------|------|--------------------|-----|---------------------|-----------------------|----------|---------------------|------------------|-------------------------|--|
| Compact PAR16 | | | | | | | | | | | | | | | | | | |
|  | MED | 4 | 26383 | LED4D/P16/NFLTP | 120 | 3 | 2.8 | 250 | 720 | 3000 | 80 | 40W | 25,000 | Yes | ★ | Dry | Accent, 35° beam, White | |
| | | 6 | 26384 | LED6D/P16/NFLTP | 120 | 3 | 2.8 | 380 | 1100 | 3000 | 80 | 60W | 25,000 | Yes | ★ | Dry | Accent, 35° beam, White | |
| Compact PAR20 | | | | | | | | | | | | | | | | | | |
|  | MED | 7 | 93327 | LED7DP203B830/20 | 120 | 6 | 3.5 | 520 | 3600 | 3000 | 80 | 70W | 25,000 | Yes | ★ | Damp | Accent, 20° beam Black | |
| | | | 93347 | LED7DP203W830/20 | 120 | 6 | 3.5 | 520 | 3600 | 3000 | 80 | 70W | 25,000 | Yes | ★ | Damp | Accent, 20° beam White | |
| | | | 93348 | LED7DP203W830/35 | 120 | 6 | 3.5 | 520 | 1200 | 3000 | 80 | 65W | 25,000 | Yes | ★ | Damp | Accent, 35° beam White | |
| | | | 93349 | LED7DP203B827/20 | 120 | 6 | 3.5 | 500 | 3600 | 2700 | 80 | 70W | 25,000 | Yes | ★ | Damp | Accent, 20° beam Black | |
| | | | 93354 | LED7DP203B827/35 | 120 | 6 | 3.5 | 500 | 1150 | 2700 | 80 | 65W | 25,000 | Yes | ★ | Damp | Accent, 35° beam Black | |
| | | | 93360 | LED7DP203W827/20 | 120 | 6 | 3.5 | 500 | 3600 | 2700 | 80 | 70W | 25,000 | Yes | ★ | Damp | Accent, 20° beam White | |
| | | | 93362 | LED7DP203W827/35 | 120 | 6 | 3.5 | 500 | 1150 | 2700 | 80 | 65W | 25,000 | Yes | ★ | Damp | Accent, 35° beam White | |

Directional Lamps (PAR30 - Low Glare - Visual Comfort Lens™)

| Bulb Shape | Base Type | Watts | Order Code | Description | Volts | Case Qty** | MOL (in) | Lumens Initial | CBCP | Initial Color Temp | CRI | Wattage Replacement | *Rated Life L70 (Hrs) | Dimmable | ENERGY STAR® Status | #Location Rating | Additional Information | |
|--|-----------|-------|------------|------------------|-------|------------|----------|----------------|------|--------------------|-----|---------------------|-----------------------|----------|---------------------|------------------|-------------------------------|--|
| Compact PAR30 - Low Glare - Visual Comfort Lens™ | | | | | | | | | | | | | | | | | | |
|  | MED | 12 | 67925 | LED12DP30R927/15 | 120 | 6 | 3.8 | 820 | 5350 | 2700 | 91 | 65W | 25,000 | Yes | | Dry | Accent, 15° beam, Silver | |
| | | | 84379 | LED12DP30RW93025 | 120 | 6 | 3.74 | 900 | 3900 | 3000 | 90 | 75W | 25,000 | Yes | ★ | Dry | Narrow Flood, 25° beam, White | |
| | | | 84380 | LED12DP30RW93040 | 120 | 6 | 3.74 | 900 | 1800 | 3000 | 90 | 75W | 25,000 | Yes | ★ | Dry | Flood, 40° beam, White | |
| | | | 84392 | LED12DP30RW92725 | 120 | 6 | 3.74 | 850 | 3500 | 2700 | 90 | 75W | 25,000 | Yes | ★ | Dry | Narrow Flood, 25° beam, White | |
| | | | 84395 | LED12DP30RW92740 | 120 | 6 | 3.74 | 850 | 1700 | 2700 | 90 | 75W | 25,000 | Yes | ★ | Dry | Flood, 40° beam, White | |
| | | | 84384 | LED12DP30RW83025 | 120 | 6 | 3.74 | 1050 | 4800 | 3000 | 80 | 75W | 25,000 | Yes | ★ | Dry | Narrow Flood, 25° beam, White | |
| | | | 42131 | LED12DP30RW83040 | 120 | 6 | 3.74 | 1050 | 2400 | 3000 | 80 | 75W | 25,000 | Yes | ★ | Dry | Flood, 40° beam, White | |
| | | | 42133 | LED12DP30RW82725 | 120 | 6 | 3.74 | 1000 | 4700 | 2700 | 80 | 75W | 25,000 | Yes | ★ | Dry | Narrow Flood, 25° beam, White | |
| | | | 73583 | LED12DP30RB82740 | 120 | 6 | 3.74 | 1000 | 2200 | 2700 | 80 | 75W | 25,000 | Yes | ★ | Dry | Flood, 40° beam, Black | |
| Compact PAR30 - Long Neck - Low Glare - Visual Comfort Lens™ | | | | | | | | | | | | | | | | | | |
|  | MED | 12 | 68390 | LED12DP3LR927/15 | 120 | 6 | 4.8 | 820 | 5350 | 2700 | 91 | 65W | 50,000 | Yes | | Dry | Accent, 15° beam, Silver | |
| | | | 68391 | LED12DP3LR927/25 | 120 | 6 | 4.8 | 820 | 2950 | 2700 | 91 | 75W | 50,000 | Yes | | Dry | Accent, 25° beam, Silver | |
| | | | 84399 | LED12DP3LRW93025 | 120 | 6 | 4.72 | 900 | 3900 | 3000 | 90 | 75W | 25,000 | Yes | ★ | Dry | Narrow Flood, 25° beam, White | |
| | | | 84400 | LED12DP3LRW93040 | 120 | 6 | 4.72 | 900 | 1800 | 3000 | 90 | 75W | 25,000 | Yes | ★ | Dry | Flood, 40° beam, White | |
| | | | 84407 | LED12DP3LRW92740 | 120 | 6 | 4.72 | 850 | 1700 | 2700 | 90 | 75W | 25,000 | Yes | ★ | Dry | Flood, 40° beam, White | |
| | | | 42136 | LED12DP3LRW83025 | 120 | 6 | 4.72 | 1050 | 4800 | 3000 | 80 | 75W | 25,000 | Yes | ★ | Dry | Narrow Flood, 25° beam, White | |
| | | | 42137 | LED12DP3LRW83040 | 120 | 6 | 4.72 | 1050 | 2400 | 3000 | 80 | 75W | 25,000 | Yes | ★ | Dry | Flood, 40° beam, White | |
| | | | 42144 | LED12DP3LRW82740 | 120 | 6 | 4.72 | 1000 | 2200 | 2700 | 80 | 75W | 25,000 | Yes | ★ | Dry | Flood, 40° beam, White | |
| | | | 20151 | LED17DP30LW93025 | 120 | 6 | 4.8 | 1100 | 4600 | 3000 | 90 | 75W | 25,000 | Yes | ★ | Damp | Spot, 25° beam, White | |

Directional Lamps (PAR30)

| Bulb Shape | Base Type | Watts | Order Code | Description | Volts | Case Qty** | MOL (in) | Lumens Initial | CBCP | Initial Color Temp | CRI | Wattage Replacement | *Rated Life L70 (Hrs) | Dimmable | ENERGY STAR® Status | #Location Rating | Additional Information | |
|--|-----------|-------|------------|------------------|-------|------------|----------|----------------|------|--------------------|-----|---------------------|-----------------------|----------|---------------------|------------------|-------------------------------|--|
| Compact PAR30 | | | | | | | | | | | | | | | | | | |
|  | MED | 12 | 94220 | LED12DP302W82735 | 120 | 6 | 3.7 | 850 | 2300 | 2700 | 84 | 85W | 25,000 | Yes | ★ | Damp | Flood, 35° beam, White | |
| | | | 98755 | LED12DP303W83035 | 120 | 6 | 3.66 | 950 | 2600 | 3000 | 80 | 85W | 25,000 | Yes | ★ | Damp | Flood, 35° beam, White, STIR | |
| Compact PAR30 Long Neck | | | | | | | | | | | | | | | | | | |
|  | MED | 12 | 98811 | LED12DP3L3W83035 | 120 | 6 | 4.61 | 950 | 2600 | 3000 | 80 | 85W | 25,000 | Yes | ★ | Damp | Accent, 35° beam, White, STIR | |

Information provided is subject to change without notice. Please verify all details with GE. All values are design or typical values when measured under laboratory conditions, and GE makes no warranty or guarantee, expressed or implied, that such performance will be obtained under end-use conditions.

* The life rating is based on the hours of operation the lamp will provide before reaching 70% of its original rating (L70)

** Minimum order quantity = 6

★ ENERGY STAR® status: ENERGY STAR® certified. Lamps without a ★ are not ENERGY STAR® certified.

UL 1993 Environmental Requirements for LED LAMPS

Location, damp - Exterior or interior location that is normally or periodically subject to condensation of moisture in, on, or adjacent to, electrical equipment, and includes partially protected locations.

Location, dry - Location not normally subject to dampness, may include a location subject to temporary dampness, i.e., building under construction, provided ventilation is adequate to prevent accumulation of moisture.

Location, wet - Location in which water or other liquid can drip, splash, or flow on or against electrical equipment.



Notes: 1) Product descriptions ending in "/TP" indicate a carded blister or clamshell package nested in a tray for shelf display. Cards also designed for hook display.

2) LED A19 Locking device works on PC: 85791, 85792, 89898, 62182, 89899 and 89900



Get more information at
GELighting.com/ThinkLED

LED replacement lamps


Directional Lamps (PAR38 - Low Glare - Visual Comfort Lens™)

| Bulb Shape | Base Type | Watts | Order Code | Description | Volts | Case Qty** | MOL (In) | Lumens Initial | CBCP | Initial Color Temp | CRI | Wattage Replacement | *Rated Life L70 (Hrs) | Dimmable | ENERGY STAR® Status | #Location Rating | Additional Information |
|--|-----------|------------------|------------------|------------------|-------|------------|----------|----------------|-------|--------------------|--------|---------------------|-----------------------|----------|-------------------------------|-------------------------------|-------------------------------|
| PAR38 - Low Glare - Visual Comfort Lens™ | | | | | | | | | | | | | | | | | |
|  | MED | 12 | 63233 | LED12DP38W830/25 | 120 | 6 | 5.3 | 1000 | 4800 | 3000 | 80 | 90W | 25,000 | Yes | | Dry | Narrow Flood, 25° beam, White |
| | | | 63323 | LED12DP38W827/25 | 120 | 6 | 5.3 | 960 | 4600 | 2700 | 80 | 90W | 25,000 | Yes | | Dry | Narrow Flood, 25° beam, White |
| | | | 63330 | LED12DP38W930/15 | 120 | 6 | 5.3 | 860 | 11400 | 3000 | 91 | 90W | 25,000 | Yes | | Dry | Spot, 15° beam, White |
| | | | 63334 | LED12DP38W927/25 | 120 | 6 | 5.3 | 820 | 3900 | 2700 | 91 | 90W | 25,000 | Yes | | Dry | Narrow Flood, 25° beam, White |
| | | | 92971 | LED12D38W3827/40 | 120 | 6 | 5.31 | 1050 | 2300 | 2700 | 81 | 100W | 25,000 | Yes | ★ | Damp | Flood, 40° beam, White |
| | 18 | 92972 | LED12D38W3830/25 | 120 | 6 | 5.31 | 1050 | 5500 | 3000 | 81 | 100W | 25,000 | Yes | ★ | Damp | Narrow Flood, 25° beam, White | |
| | | 92923 | LED18D38W3927/25 | 120 | 6 | 5.31 | 1250 | 4900 | 2700 | 92 | 100W | 25,000 | Yes | ★ | Damp | Narrow Flood, 25° beam, White | |
| | | 92933 | LED18D38W3930/25 | 120 | 6 | 5.31 | 1350 | 5200 | 3000 | 92 | 100W | 25,000 | Yes | ★ | Damp | Narrow Flood, 25° beam, White | |
| | | 92934 | LED18D38W3930/40 | 120 | 6 | 5.12 | 1350 | 3200 | 3000 | 92 | 120W | 25,000 | Yes | ★ | Damp | Flood, 40° beam, White | |
| | | 92958 | LED18D38W382740 | 120 | 6 | 5.12 | 1550 | 3800 | 2700 | 81 | 120W | 25,000 | Yes | ★ | Wet | Flood, 40° beam, White | |
|  | 92963 | LED18D38W383025 | 120 | 6 | 5.12 | 1550 | 6000 | 3000 | 81 | 120W | 25,000 | Yes | ★ | Wet | Narrow Flood, 25° beam, White | | |
| | 92967 | LED18D38W383040 | 120 | 6 | 5.12 | 1550 | 4000 | 3000 | 81 | 150W | 25,000 | Yes | ★ | Wet | Flood, 40° beam, White | | |
| | 92926 | LED18D38W3927/40 | 120 | 6 | 5.12 | 1250 | 2900 | 2700 | 92 | 120W | 25,000 | Yes | ★ | Damp | Flood, 40° beam, White | | |
| | 93172 | LED18D38W384040 | 120 | 6 | 5.31 | 1700 | 4400 | 4000 | 81 | 150W | 25,000 | Yes | ★ | Wet | Flood, 40° beam, White | | |
| | 65730 | LED18D38W385025 | 120 | 6 | 5.31 | 1700 | 6500 | 5000 | 81 | 120W | 25,000 | Yes | ★ | Wet | Narrow Flood, 25° beam, White | | |
| | 65731 | LED18D38W385040 | 120 | 6 | 5.31 | 1700 | 4400 | 5000 | 81 | 150W | 25,000 | Yes | ★ | Wet | Flood, 40° beam, White | | |



Directional Lamps (Commercial PAR38)

| Bulb Shape | Base Type | Watts | Order Code | Description | Volts | Case Qty** | MOL (In) | Lumens Initial | CBCP | Initial Color Temp | CRI | Wattage Replacement | *Rated Life L70 (Hrs) | Dimmable | ENERGY STAR® Status | #Location Rating | Additional Information | |
|--|-----------|-----------------|------------------|------------------|------------------|------------|----------|----------------|------|--------------------|--------|---------------------|-----------------------|----------|---|-------------------------------------|--------------------------------|-------------------------------|
| Commercial PAR38 (Indoor/Outdoor) | | | | | | | | | | | | | | | | | | |
|  | MED | 12 | 90132 | LED12DP382W82725 | 120 | 6 | 5.1 | 850 | 4000 | 2700 | 84 | 85W | 25,000 | Yes | ★ | Wet | Narrow Flood, 25° beam, White | |
| | | | 18 | 90154 | LED18DP38W827/25 | 120 | 6 | 5.1 | 1200 | 7000 | 2700 | 84 | 100W | 25,000 | Yes | ★ | Wet | Narrow Flood, 25° beam, White |
| | | | 90162 | LED18DP38W840/25 | 120 | 6 | 5.1 | 1400 | 8200 | 4000 | 84 | 100W | 25,000 | Yes | ★ | Wet | Narrow Flood, 25° beam, White | |
| | | | 26 | 68183 | LED26DP38S830/12 | 120 | 6 | 5.3 | 1500 | 24000 | 3000 | 82 | 130W | 25,000 | Yes | ★ | Wet | Spot, 12° beam, Silver |
| | | | 68184 | LED26DP38S830/25 | 120 | 6 | 5.3 | 1500 | 6800 | 3000 | 82 | 130W | 25,000 | Yes | ★ | Wet | Narrow Flood, 25° beam, Silver | |
| | 28 | 68185 | LED26DP38S830/40 | 120 | 6 | 5.3 | 1500 | 3100 | 3000 | 82 | 120W | 25,000 | Yes | ★ | Wet | Flood, 40° beam, Silver | | |
| | | 68182 | LED26DP38S840/40 | 120 | 6 | 5.3 | 1650 | 3200 | 4000 | 82 | 120W | 25,000 | Yes | ★ | Wet | Flood, 40° beam, Silver | | |
| | | 33647 | LED26DP38S835/12 | 120 | 6 | 5.3 | 1900 | 31000 | 3500 | 82 | 160W | 25,000 | Yes | ★ | Wet | Spot, 12° beam, Silver | | |
| | | 70591 | LED26DP38S835/40 | 120 | 6 | 5.3 | 1900 | 4000 | 3500 | 82 | 160W | 25,000 | Yes | ★ | Wet | Flood, 40° beam, Silver | | |
| | | 15139 | LED28P38S830/15 | 120 | 6 | 5.3 | 2400 | 20000 | 3000 | 81 | 150W | 25,000 | - | ★ | Dry | Spot, 15° beam, Silver, Non-Dimming | | |
|  | 25844 | LED28P38S830/25 | 120 | 6 | 5.31 | 2400 | 11,000 | 3000 | 81 | 150W | 25,000 | - | ★ | Dry | Narrow Flood, 25° beam, Silver, Non-Dimming | | | |
| | 25953 | LED28P38S830/40 | 120 | 6 | 5.31 | 2400 | 5,600 | 3000 | 81 | 150W | 25,000 | - | ★ | Dry | Flood, 40° beam, Silver, Non-Dimming | | | |

LED HID

| Bulb Shape | Base Type | Watts | Order Code | Description | Volts | Case Qty** | MOL (In) | Lumens Initial | CBCP | Initial Color Temp | CRI | Wattage Replacement | *Rated Life L70 (Hrs) | Dimmable | ENERGY STAR® Status | #Location Rating | Additional Information |
|--|-----------|-------|------------|-------------|-----------------|------------|----------|----------------|--------|--------------------|-----|---------------------|-----------------------|----------|---------------------|------------------|------------------------------------|
| 400 Watt Metal Halide Replacement Lamp | | | | | | | | | | | | | | | | | |
|  | ED37 | EX39 | 165 | 21259 | LED165/M400/740 | | 3 | 11.42 | 20,000 | 4000 | 73 | 400 | 50,000 | - | | Dry | Open Rated, ANSI - M59, M135, M155 |

Plug-In

| Bulb Shape | Base Type | Watts | Order Code | Description | Volts | Case Qty** | MOL (In) | Lumens Initial | CBCP | Initial Color Temp | CRI | Wattage Replacement | *Rated Life L70 (Hrs) | Dimmable | ENERGY STAR® Status | #Location Rating | Additional Information |
|--|-----------|-----------|------------|-------------|-----------------|------------|----------|----------------|------|--------------------|-----|---------------------|-----------------------|----------|---------------------|------------------|------------------------------------|
| Vertical | | | | | | | | | | | | | | | | | |
|  | Plug-In | G24q/GX24 | 12 | 96801 | LED12G24Q-V/827 | # | 6 | 5.31 | 950 | 2700 | 80 | | 50000 | - | | Damp | Requires Electronic Ballast, White |
| | | | | 96775 | LED12G24Q-V/830 | # | 6 | 5.31 | 950 | 3000 | 80 | | 50000 | - | | Damp | Requires Electronic Ballast, White |
| | | | | 96689 | LED12G24Q-V/835 | # | 6 | 5.31 | 1000 | 3500 | 80 | | 50000 | - | | Damp | Requires Electronic Ballast, White |
| | | | | 96771 | LED12G24Q-V/840 | # | 6 | 5.31 | 1000 | 4000 | 80 | | 50000 | - | | Damp | Requires Electronic Ballast, White |
| Horizontal | | | | | | | | | | | | | | | | | |
|  | Plug-In | G24q/GX24 | 12 | 96799 | LED12G24Q-H/827 | # | 6 | 5.31 | 950 | 2700 | 80 | | 50000 | - | | Damp | Requires Electronic Ballast, White |
| | | | | 96798 | LED12G24Q-H/830 | # | 6 | 5.31 | 950 | 3000 | 80 | | 50000 | - | | Damp | Requires Electronic Ballast, White |
| | | | | 96761 | LED12G24Q-H/835 | # | 6 | 5.31 | 1000 | 3500 | 80 | | 50000 | - | | Damp | Requires Electronic Ballast, White |
| | | | | 96769 | LED12G24Q-H/840 | # | 6 | 5.31 | 1000 | 4000 | 80 | | 50000 | - | | Damp | Requires Electronic Ballast, White |

- Check compatibility at GELighting.com/LED4pin-compatibility

Information provided is subject to change without notice. Please verify all details with GE. All values are design or typical values when measured under laboratory conditions, and GE makes no warranty or guarantee, expressed or implied, that such performance will be obtained under end-use conditions.

* The life rating is based on the hours of operation the lamp will provide before reaching 70% of its original rating (L70)

** Minimum order quantity = 6

★ ENERGY STAR® status: ENERGY STAR® certified. Lamps without a ★ are not ENERGY STAR® certified.

UL 1993 Environmental Requirements for LED LAMPS

Location, damp - Exterior or interior location that is normally or periodically subject to condensation of moisture in, on, or adjacent to, electrical equipment, and includes partially protected locations.

Location, dry - Location not normally subject to dampness, may include a location subject to temporary dampness, i.e., building under construction, provided ventilation is adequate to prevent an accumulation of moisture.

Location, wet - Location in which water or other liquid can drip, splash, or flow on or against electrical equipment.

Notes: 1) Product descriptions ending in "/TP" indicate a carded blister or clamshell package nested in a tray for shelf display. Cards also designed for hook display. 2) LED A19 Locking device works on PC: 85791, 85792, 89898, 62182, 89899 and 89900

Get more information at
GELighting.com/ThinkLED

LED replacement lamps

RS Cans

| Bulb Shape | Base Type | Watts | Order Code | Description | Volts | Case Qty** | MOL (In) | Lumens Initial | CBCP | Initial Color Temp | CRI | Wattage Replacement | *Rated Life L70 (Hrs) | Dimmable | ENERGY STAR® Status | #Location Rating | Additional Information | |
|--|-----------|-------|------------|------------------|------------------|------------|----------|----------------|------|--------------------|------|---------------------|-----------------------|----------|---------------------|------------------|----------------------------|----------------------------|
| RS Cans | | | | | | | | | | | | | | | | | | |
|  | E26 | 10 | 95853 | LED10RS4/827E26P | 120 | 12 | 5.88 | 700 | | 2700 | 80 | 65W | 50,000 | Yes | ★ | Damp | 4" Can, Pigtail Attachment | |
| | | | | 95854 | LED10RS4/830E26P | 120 | 12 | 5.88 | 700 | | 3000 | 80 | 65W | 50,000 | Yes | ★ | Damp | 4" Can, Pigtail Attachment |
| | GU24 | | | 95855 | LED10RS4/827GUP | 120 | 12 | 5.88 | 700 | | 2700 | 80 | 65W | 50,000 | Yes | ★ | Damp | 4" Can, Pigtail Attachment |
| | | | | 95856 | LED10RS4/830GUP | 120 | 12 | 5.88 | 700 | | 3000 | 80 | 65W | 50,000 | Yes | ★ | Damp | 4" Can, Pigtail Attachment |
| | E26 | | | 85153 | LED10RS6/827E26P | 120 | 12 | 7.5 | 700 | | 2700 | 80 | 65W | 50,000 | Yes | ★ | Damp | 6" Can, Pigtail Attachment |
| | | | | 85160 | LED10RS6/830E26P | 120 | 12 | 7.5 | 700 | | 3000 | 80 | 65W | 50,000 | Yes | ★ | Damp | 6" Can, Pigtail Attachment |
| | GU24 | | | 95851 | LED10RS6/827GUP | 120 | 12 | 7.5 | 700 | | 2700 | 80 | 65W | 50,000 | Yes | ★ | Damp | 6" Can, Pigtail Attachment |
| | | | | 95852 | LED10RS6/830GUP | 120 | 12 | 7.5 | 700 | | 3000 | 80 | 65W | 50,000 | Yes | ★ | Damp | 6" Can, Pigtail Attachment |
| | E26 | 13 | | 70120 | LED13RS6/827E26P | 120 | 12 | 7.5 | 1000 | | 2700 | 80 | 90w | 50,000 | Yes | ★ | Damp | 6" Can, Pigtail Attachment |
| | | | | 70122 | LED13RS6/830E26P | 120 | 12 | 7.5 | 1000 | | 3000 | 80 | 90w | 50,000 | Yes | ★ | Damp | 6" Can, Pigtail Attachment |
| | GU24 | | | 70124 | LED13RS6/827GUP | 120 | 12 | 7.5 | 1000 | | 2700 | 80 | 90w | 50,000 | Yes | ★ | Damp | 6" Can, Pigtail Attachment |
| | | | | 70127 | LED13RS6/830GUP | 120 | 12 | 7.5 | 1000 | | 3000 | 80 | 90w | 50,000 | Yes | ★ | Damp | 6" Can, Pigtail Attachment |

LED Tubes

Integrated and Refit

| Type | Base Type | Watts | Order Code | Description | Volts | Case Qty** | MOL (In) | Lumens Initial | Initial Color Temp | CRI | Wattage Replacement | *Rated Life L70 (Hrs) | DLC | UL | #Location Rating | Additional Information | |
|---|-----------|-------|----------------|------------------|-------|------------|-----------|----------------|--------------------|-----|---------------------|-----------------------|-----|-----|------------------|----------------------------------|--|
| Integrated 4ft LED Tubes (operates on Instant Start or Program Start Ballast) | | | | | | | | | | | | | | | | | |
| T8 | G13 | 18 | 31550 | LED18ET8/4/830 | | 25 | 48 | 2200 | 3000K | 80+ | | 50,000 | Yes | Yes | Damp | Dimmability Requires PRS Ballast | |
| | G13 | 18 | 93133 | LED18ET8/4/835 | | 25 | 48 | 2200 | 3500K | 80+ | | 50,000 | Yes | Yes | Damp | Dimmability Requires PRS Ballast | |
| | G13 | 18 | 93135 | LED18ET8/4/840 | | 25 | 48 | 2200 | 4000K | 80+ | | 50,000 | Yes | Yes | Damp | Dimmability Requires PRS Ballast | |
| | G13 | 18 | 93140 | LED18ET8/4/850 | | 25 | 48 | 2200 | 5000K | 80+ | | 50,000 | Yes | Yes | Damp | Dimmability Requires PRS Ballast | |
| Integrated 3ft LED Tubes (operates on Instant Start or Program Start Ballast) | | | | | | | | | | | | | | | | | |
| G13 | 12 | 31554 | LED12ET8/3/830 | | 25 | 36 | 1400 | 3000K | 80+ | | | 50,000 | - | Yes | Damp | Dimmability Requires PRS Ballast | |
| | 12 | 26544 | LED12ET8/3/835 | | 25 | 36 | 1400 | 3500K | 80+ | | | 50,000 | - | Yes | Damp | Dimmability Requires PRS Ballast | |
| | 12 | 26625 | LED12ET8/3/840 | | 25 | 36 | 1400 | 4000K | 80+ | | | 50,000 | - | Yes | Damp | Dimmability Requires PRS Ballast | |
| | 12 | 26627 | LED12ET8/3/850 | | 25 | 36 | 1400 | 5000K | 80+ | | | 50,000 | - | Yes | Damp | Dimmability Requires PRS Ballast | |
| Integrated 2ft LED Tubes (operates on Instant Start or Program Start Ballast) | | | | | | | | | | | | | | | | | |
| G13 | 9 | 31557 | LED9ET8/2/830 | | 25 | 24 | 1100 | 3000K | 80+ | | | 50,000 | - | Yes | Damp | Dimmability Requires PRS Ballast | |
| | 9 | 26635 | LED9ET8/2/835 | | 25 | 24 | 1100 | 3500K | 80+ | | | 50,000 | - | Yes | Damp | Dimmability Requires PRS Ballast | |
| | 9 | 26648 | LED9ET8/2/840 | | 25 | 24 | 1100 | 4000K | 80+ | | | 50,000 | - | Yes | Damp | Dimmability Requires PRS Ballast | |
| | 9 | 26676 | LED9ET8/2/850 | | 25 | 24 | 1100 | 5000K | 80+ | | | 50,000 | - | Yes | Damp | Dimmability Requires PRS Ballast | |
| Refit 4 ft LED Tubes (operates with Remote Driver) | | | | | | | | | | | | | | | | | |
| T8 | G13 | 16 | 88138 | LED18T8/4/850/BT | | 25 | 48 | 2300 | 5000K | 80+ | | 50,000 | Yes | Yes | Damp | Requires Driver / Dimming Driver | |
| | G13 | 18 | 94381 | LED21T8/4/835 | | 10 | 48 | 2100 | 3500K | 80+ | | 50,000 | Yes | Yes | Damp | Requires Driver / Dimming Driver | |
| | G13 | 18 | 94382 | LED21T8/4/840 | | 10 | 48 | 2100 | 4000K | 80+ | | 50,000 | Yes | Yes | Damp | Requires Driver / Dimming Driver | |
| | G13 | 18 | 94383 | LED21T8/4/850 | | 10 | 48 | 2200 | 5000K | 80+ | | 50,000 | Yes | Yes | Damp | Requires Driver / Dimming Driver | |
| | G13 | 18 | 26059 | LED21T8/4/865 | | 10 | 48 | 2200 | 6500K | 80+ | | 50,000 | - | Yes | Damp | Requires Driver / Dimming Driver | |
| | G13 | 18 | 62428 | LED21T8/G/4/835 | | 10 | 48 | 2200 | 3500K | 80+ | | 50,000 | Yes | Yes | Damp | Requires Driver / Dimming Driver | |
| | G13 | 18 | 62485 | LED21T8/G/4/840 | | 10 | 48 | 2200 | 4000K | 80+ | | 50,000 | Yes | Yes | Damp | Requires Driver / Dimming Driver | |
| | G13 | 18 | 62487 | LED21T8/G/4/850 | | 10 | 48 | 2300 | 5000K | 80+ | | 50,000 | Yes | Yes | Damp | Requires Driver / Dimming Driver | |
| Refit 3 ft LED Tubes (Operates with Remote Driver) | | | | | | | | | | | | | | | | | |
| T8 | G13 | 16 | 82343 | LED18T8/3/835 | | 10 | 36 | 1800 | 3500K | 80+ | | 50,000 | - | Yes | Damp | Requires Driver / Dimming Driver | |
| | G13 | 16 | 82345 | LED18T8/3/840 | | 10 | 36 | 1800 | 4000K | 80+ | | 50,000 | - | Yes | Damp | Requires Driver / Dimming Driver | |
| | G13 | 16 | 82346 | LED18T8/3/850 | | 10 | 36 | 1800 | 5000K | 80+ | | 50,000 | - | Yes | Damp | Requires Driver / Dimming Driver | |
| Refit 2 ft LED Tubes (Operates with Remote Driver) | | | | | | | | | | | | | | | | | |
| T8 | G13 | 8 | 92997 | LED9T8/2/865 | | 20 | 24 | 900 | 6500K | 80+ | | 50,000 | - | Yes | Damp | Requires Driver / Dimming Driver | |
| | G13 | 8 | 65706 | LED9T8/2/835 | | 20 | 24 | 900 | 3500K | 80+ | | 50,000 | Yes | Yes | Damp | Requires Driver / Dimming Driver | |
| | G13 | 8 | 65707 | LED9T8/2/840 | | 20 | 24 | 900 | 4000K | 80+ | | 50,000 | Yes | Yes | Damp | Requires Driver / Dimming Driver | |
| | G13 | 8 | 65711 | LED9T8/2/850 | | 20 | 24 | 900 | 5000K | 80+ | | 50,000 | Yes | Yes | Damp | Requires Driver / Dimming Driver | |
| Refit LED U-Tubes (Operates with Remote Driver) | | | | | | | | | | | | | | | | | |
| T8 | G13 | 12 | 28084 | LED14T8/U/835 | | 15 | U - 1 5/8 | 1700 | 3500K | 80+ | | 50,000 | - | Yes | Damp | Requires Driver / Dimming Driver | |
| | G13 | 12 | 28164 | LED14T8/U/840 | | 15 | U - 1 5/8 | 1700 | 4000K | 80+ | | 50,000 | - | Yes | Damp | Requires Driver / Dimming Driver | |

Information provided is subject to change without notice. Please verify all details with GE. All values are design or typical values when measured under laboratory conditions, and GE makes no warranty or guarantee, expressed or implied, that such performance will be obtained under end-use conditions.

* The life rating is based on the hours of operation the lamp will provide before reaching 70% of its original rating (L70)
 ** Minimum order quantity = 6

UL 1993 Environmental Requirements for LED LAMPs
 Location, damp - Exterior or interior location that is normally or periodically subject to condensation of moisture in, on, or adjacent to, electrical equipment, and includes partially protected locations.
 Location, dry - Location not normally subject to dampness, may include a location subject to temporary dampness, i.e., building under construction, provided ventilation is adequate to prevent an accumulation of moisture.
 Location, wet - Location in which water or other liquid can drip, splash, or flow on or against electrical equipment.

Notes: 1) Product descriptions ending in "/TP" indicate a carded blister or clamshell package nested in a tray for shelf display. Cards also designed for hook display.
 2) LED A19 Locking device works on PC: 85791, 85792, 89898, 62182, 89899 and 89900

Get more information at
GELighting.com/ThinkLED

LED Drivers

Remote Drivers

| Type | Base Type | Watts | Order Code | Description | Volts | Case Qty** | Output Current (A) | Frequency | Eff | Output | Output Voltage | Temp (Min) | Temp (Max) | Dimmable | Additional Information |
|---------------------------------------|-----------|-------|------------|------------------|----------|------------|--------------------|-----------|-----|--------|----------------|------------|------------|----------|------------------------------|
| Lightech Drivers - Non-Dimming | | | | | | | | | | | | | | | |
| | | 18 | 93100 | LED9T8/DR/UN/2L | 120-277V | 10 | 0.27x2 | 50/60 Hz | >.9 | DC | 27-33V | -4 F | 104 F | - | Maximum 2 Tubes (non potted) |
| | | 36 | 82347 | LED18T8/DR/UN/2L | 120-277V | 10 | 0.35 | 50/60 Hz | >.9 | DC | 27-33V | -4 F | 104 F | - | Maximum 2 Tube (non potted) |
| | | 21 | 94384 | LED21T8/DR/1L | 120-277V | 10 | 0.62 | 50/60 Hz | >.9 | DC | 27-33V | -4 F | 104 F | - | Maximum 1 Tube |
| | | 42 | 94385 | LED21T8/DR/2L | 120-277V | 10 | 0.62x2 | 50/60 Hz | >.9 | DC | 27-33V | -4 F | 104 F | - | Maximum 2 Tube |
| Lightech Drivers - Dimming | | | | | | | | | | | | | | | |
| | | 36 | 88141 | LED18T8/DR/D2L | 120-277V | 10 | 0.53x2 | 50/60 Hz | >.9 | DC | 27-33V | -4 F | 104 F | Yes | Maximum 2 Tube |
| | | 72 | 88139 | LED18T8/DR/D4L | 120-277V | 10 | 0.53x4 | 50/60 Hz | >.9 | DC | 27-33V | -4 F | 104 F | Yes | Maximum 4 Tube |
| | | 42 | 60041 | LED21T8/DR/D2L | 120-277V | 10 | 0.62x2 | 50/60 Hz | >.9 | DC | 27-33V | -4 F | 104 F | Yes | Maximum 2 Tube |
| | | 84 | 62030 | LED21T8/DR/D4L | 120-277V | 10 | 0.62x4 | 50/60 Hz | >.9 | DC | 27-33V | -4 F | 104 F | Yes | Maximum 4 Tube |
| | | 42 | 28174 | LED14/DR/D3L | 120-277V | 10 | 0.43x3 | 50/60 Hz | >.9 | DC | 27-33V | -4 F | 104 F | Yes | Maximum 3 Tube |

Awaken like never before the moment you turn on GE's LED replacement lamp.

Light influences people's emotions, how they view their space and their world, and how they start and end their day. GE understands this and wants to help transform your stores, buildings or facilities, while ensuring your upfront investment is paid back as quickly as possible.

If you're inspired to enhance your space — with substantial savings — call your GE Lighting representative.

To experience what we've done for our existing customers, see case studies, videos and image galleries at gelighting.com/ThinkLED



Product is compliant with material restriction requirements of RoHS

ENERGY STAR® is a registered U.S. mark



www.gelighting.com

GE and the GE Monogram are trademarks of the General Electric Company. All other trademarks are the property of their respective owners. Information provided is subject to change without notice. All values are design or typical values when measured under laboratory conditions. GE Lighting and GE Lighting Solutions, LLC are businesses of the General Electric Company. © 2015 GE.

78945 (Rev 12/04/2015)