

Round Flush Mount

LED

40 Watt 2900lms Round Flush Mount Specifications



The ETi 40 watt 2900 lumen LED round flush mount fixture offers exceptional performance for precision lighting applications, while reducing energy and maintenance cost when compared with conventional light sources. Lasting over 10 times longer, these flush mount fixtures are high quality replacements for incandescent flush mount fixtures and is available in 4000K. They are UL listed for use in damp and dry locations. Warranty 5 years. Suitable for installations from - 4° F to 95° F.


KEY FEATURES & BENEFITS

- 40 Watt Low Power and High Performance
- 2900 lumens
- Dimmable
- 84 CRI , 4000K
- UL-Damp and Dry Locations
- Replaces most applications using 300w incandescent lamps
- Rated life 35,000 hours



This light source meets restrictions on hazardous substances.

FIXTURE DIMENSIONS



SKU# 54614142

Dimension A = 24.0"

Dimension B = 4.6"

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation. For FCC Part 15 user information, please see www.etiled.us/fcc15b

APPLICATION INFORMATION

Designed to be used anywhere a standard incandescent fixture is used. Typically used in bedrooms, hallways, kitchens, living rooms and recreational rooms. Other applications apply in commercial, office, retail, restaurants, schools, hospitals and hotel/motel locations.



855-384-7754 www.etissl.com

40 Watt 2900lms Round Flush Mount

LED

SPECIFICATION DATA

Project _____

Item Number _____

Prepared by _____ Date _____

ORDERING INFORMATION

Item Number	Description	Wattage	Input Voltage (VAC)	Average Rated Life ¹	Typical Lumens ²	CCT ³	CRI ⁴	Power Factor	R9	Duv	CBCP	Beam	Operating Frequency
54614142	LED40w FLUSH-MOUNT 840120 DIM	40	120	35,000	2900	4000K	90.9	>.99	57	-0.00206	886	116	60Hz
¹ Hours lifetime with 70% lumen maintenance													
² Thermally stable typical lumens (±10%)													
³ Thermally stable CCT (±10%)													
⁴ Color rendering index/Ra													

SHIPPING INFORMATION

Item Number	Item UPC	Item Dimensions (H x L x W)	Item Weight (lbs)	Inner Pack Qty	Inner Carton Bar Code	Inner Carton Dimensions (H x L x W)	Inner Pack Weight (lbs)	Master Pack Qty	Master Carton Bar Code	Master Dimensions (H x L x W)	Master Pack Weight (lbs)
54614142	836607009098	26" x 25.9" x 6"	4.3	N/A	N/A	N/A	N/A	2	50836607009093	27.2" x 26.5" x 12.8"	17



LED lighting facts
A Program of the U.S. DOE

Light Output (Lumens) 2900
Watts 40
Lumens per Watt (Effucacy) 73

Color Accuracy
Color Rendering Index (CRI) 84

Light Color
Correlated Color Temperature (CCT) 4000 (Bright White)

2700K 3000K 4500K 6500K

All results are according to IESNA LM-79-2008: Approved Method for the Electrical and Photometric Testing of Solid-State Lighting. The U.S. Department of Energy (DOE) verifies product test data and results.
Visit www.lightingfacts.com for the Label Reference Guide.
Registration Number: YN84-KEBC4 (4/30/2014)
Model Number: 546141XX ("XX" can be 41-50)
Type: Surface-mounted fixture (other)

ADA Compliant

Meets American with Disabilities Act standard extension requirements.

The Americas Headquarters
26650 Renaissance Parkway, STE 6
Cleveland, OH 44128

855-384-7754 www.etissl.com