



GE  
Lighting

68920 - F32T8/SPX30/U6/2

F32T8/SPX30/U6/2

Product Photo



#### GENERAL CHARACTERISTICS

Base Description	Medium Bi-Pin
Base Type	Pin/Plug-In
Mercury Content	90 mg
Mercury-Picogram per mean lm hr	1711
Starting Temp (MIN) C-degrees	10 °C
Bulb Material	Sodalime glass
Rated Life Hours-nominal	20000 h
Primary Application	Full Wattage
Product Technology	Linear Fluorescent
Base	G13
Bulb Shape	T8

#### PHOTOMETRIC CHARACTERISTICS

Mean Lumens nominal	2630 lm
Nominal Initial Lumen per Watt	88
Initial Lumens-nominal	2800 lm
Color Rendering Index-CRI	82
Color Temperature	3000 K

#### PRODUCT INFORMATION

Product Code	68920
Description	F32T8/SPX30/U6/2
Alternative Unit Of Measure	Case
Standard Package Quantity	12
Ean UPC	043168689205
Standard Package GTIN	10043168689202
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	12
Sales Unit	Unit
UCC	043168689205

#### DIMENSIONS

Diameter	1 in
Nominal Length	22.5 in

#### ELECTRICAL CHARACTERISTICS

Rated power (Watts)	32 W
---------------------	------