



GE
Lighting

66471 - F28T8/XLSP35ECO-T8-SPP NEW TECHNICAL LAMPS

F28T8/XL/SPP35/ECO

☞ Meets TCLP requirements

Product Photo



GENERAL CHARACTERISTICS

| | |
|---------------------------------|---------------------------------|
| Base Description | Medium Bi-Pin |
| Base Type | Pin/Plug-In |
| Mercury Content | 2.95 mg |
| Mercury-Picogram per mean lm hr | 30.2 |
| Rated Life Instant Start-Hrs | 20000 h @ 3 h 28000 h @ 12 h |
| Rated Life Rapid Start - Hrs | 40000 h @ 3 h 45000 h @ 12 h |
| Starting Temp (MIN) C-degrees | 15 °C |
| Bulb Material | Sodalime glass |
| Rated Life Hours-nominal | 40000 h |
| Primary Application | Energy Saving |
| Product Technology | Linear Fluorescent |
| Base | G13 |
| Bulb Shape | T8 |

PHOTOMETRIC CHARACTERISTICS

| | |
|--------------------------------|---------|
| Mean Lumens nominal | 2440 lm |
| Nominal Initial Lumen per Watt | 93 |
| Initial Lumens-nominal | 2600 lm |
| Color Rendering Index-CRI | 80 |
| Color Temperature | 3500 K |

PRODUCT INFORMATION

| | |
|-----------------------------|--------------------|
| Product Code | 66471 |
| Description | F28T8/XL/SPP35/ECO |
| Alternative Unit Of Measure | Case |

DIMENSIONS

| | |
|----------------|-------|
| Diameter | 1 in |
| Nominal Length | 48 in |

ELECTRICAL CHARACTERISTICS

| | |
|---------------------|------|
| Rated power (Watts) | 28 W |
|---------------------|------|