



GE
Lighting

66473 - F28T8/XLSP50ECO-T8-SPP NEW TECHNICAL LAMPS

F28T8/XL/SPP50/ECO

☞ Meets TCLP requirements

Product Photo



GENERAL CHARACTERISTICS

Base Description	Medium Bi-Pin
Base Type	Pin/Plug-In
Mercury Content	2.95 mg
Mercury-Picogram per mean lm hr	30.2
Rated Life Instant Start-Hrs	20000 h @ 3 h 28000 h @ 12 h
Rated Life Rapid Start - Hrs	40000 h @ 3 h 45000 h @ 12 h
Starting Temp (MIN) C-degrees	15 °C
Bulb Material	Sodalime glass
Rated Life Hours-nominal	40000 h
Primary Application	Energy Saving
Product Technology	Linear Fluorescent
Base	G13
Bulb Shape	T8

PHOTOMETRIC CHARACTERISTICS

Mean Lumens nominal	2440 lm
Nominal Initial Lumen per Watt	93
Initial Lumens-nominal	2600 lm
Color Rendering Index-CRI	80
Color Temperature	5000 K

PRODUCT INFORMATION

Product Code	66473
Description	F28T8/XL/SPP50/ECO
Alternative Unit Of Measure	Case

DIMENSIONS

Diameter	1 in
Nominal Length	48 in

ELECTRICAL CHARACTERISTICS

Rated power (Watts)	28 W
---------------------	------