



GE
Lighting

68857 - F32T8/XL/SPX50E2

F32T8/XL/SPX50E2

Product Photo



GENERAL CHARACTERISTICS

Base Description	Medium Bi-Pin
Base Type	Pin/Plug-In
Mercury Content	2.95 mg
Mercury-Picogram per mean lm hr	27.3
Rated Life Instant Start-Hrs	25000 h @ 3 h 36000 h @ 12 h
Rated Life Rapid Start - Hrs	40000 h @ 3 h 45000 h @ 12 h
Starting Temp (MIN) C-degrees	10 °C
Bulb Material	Sodalime glass
Rated Life Hours-nominal	40000 h
Primary Application	Full Wattage
Product Technology	Linear Fluorescent
Base	G13
Bulb Shape	T8

PHOTOMETRIC CHARACTERISTICS

Mean Lumens nominal	2700 lm
Nominal Initial Lumen per Watt	90
Initial Lumens-nominal	2850 lm
Color Rendering Index-CRI	82
Color Temperature	5000 K

PRODUCT INFORMATION

Product Code	68857
Description	F32T8/XL/SPX50E2
Alternative Unit Of Measure	Case
Standard Package Quantity	36
Ean UPC	043168688574
Standard Package GTIN	10043168688571
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	36
Sales Unit	Unit
UCC	043168688574

DIMENSIONS

Diameter	1 in
Nominal Length	48 in

ELECTRICAL CHARACTERISTICS

Rated power (Watts)	32 W
---------------------	------