



GE
Lighting

68858 - F32T8/XL/SPX65E2

F32T8/XL/SPX65E2

Product Photo



GENERAL CHARACTERISTICS

Base Description	Medium Bi-Pin
Base Type	Pin/Plug-In
Mercury Content	2.95 mg
Mercury-Picogram per mean lm hr	28.3
Rated Life Instant Start-Hrs	25000 h @ 3 h 36000 h @ 12 h
Rated Life Rapid Start - Hrs	40000 h @ 3 h 45000 h @ 12 h
Starting Temp (MIN) C-degrees	10 °C
Bulb Material	Sodalime glass
Rated Life Hours-nominal	40000 h
Primary Application	Full Wattage
Product Technology	Linear Fluorescent
Base	G13
Bulb Shape	T8

PHOTOMETRIC CHARACTERISTICS

Mean Lumens nominal	2610 lm
Nominal Initial Lumen per Watt	89
Initial Lumens-nominal	2850 lm
Color Rendering Index-CRI	78
Color Temperature	6500 K

PRODUCT INFORMATION

Product Code	68858
Description	F32T8/XL/SPX65E2
Alternative Unit Of Measure	Case
Standard Package Quantity	36
Ean UPC	043168688581
Standard Package GTIN	10043168688588
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	36
Sales Unit	Unit
UCC	043168688581

DIMENSIONS

Diameter	1 in
Nominal Length	48 in

ELECTRICAL CHARACTERISTICS

Rated power (Watts)	32 W
---------------------	------