

Refit solutions from GE



Type C LED Tubes – T5 Glass

DESCRIPTION

Convert your existing linear fluorescent fixture to LED lighting without needing a comprehensive reinstall. LED tubes are ideal for those seeking high energy savings with minimal installation time. Each LED tube is operated by a GE Lightech™ driver. See reverse for LED tubes and Lightech driver product details.

FEATURES

- T5 glass tube
- 1800-4500 lumen options available
- > 270 degree beam spread
- > 120 total system lumens per watt (LPW)
- 3000K, 3500K, 4000K, 5000K and 6500K color temperature
- 50,000-hour rated life
- 5 year warranty
- UL and CUL-approved technologies
 - in compliance with UL 1598 certification

BENEFITS

- Fast and Easy LED upgrade
- Low energy LFL replacement
- 66% longer life than LFL (50,000 vs. 30,000 hours)
- Better quality of light – instant on
- Fully illuminates fixture - 270° light distribution
- Easy disposal, non-hazardous waste

ecomaginationSM

To learn more about saving money and energy,
go to: gelighting.com/ThinkLED

When you Think LED lighting, Think GE.



imagination at work

Information provided is subject to change without notice. Please verify all details with GE. All values are design or typical values when measured under laboratory conditions, and GE makes no warranty or guarantee, expressed or implied, that such performance will be obtained under end-use conditions.

Product Specifications

| Type | Base Type | Watts | Order Code | Description | Volts | Case Qty" | MOL (In) | Lumens Initial | Initial Color Temp | CRI | *Rated Life L70 (Hrs) | DLC | UL | #Location Rating | Additional Information |
|--|-----------|-------|------------|-----------------|-------|-----------|----------|----------------|--------------------|-----|-----------------------|-----|-----|------------------|------------------------|
| Remote LED Glass T5 2ft Tubes (Operates on Remote Driver) | | | | | | | | | | | | | | | |
| | G5 | 13 | 76150 | LED15T5/G/2/830 | | 20 | 22 | 1800 | 3000K | 80+ | 50,000 | - | Yes | Damp | Requires Driver |
| | G5 | 13 | 76164 | LED15T5/G/2/835 | | 20 | 22 | 1850 | 3500K | 80+ | 50,000 | - | Yes | Damp | Requires Driver |
| | G5 | 13 | 76129 | LED15T5/G/2/840 | | 20 | 22 | 1900 | 4000K | 80+ | 50,000 | - | Yes | Damp | Requires Driver |
| | G5 | 13 | 76167 | LED15T5/G/2/850 | | 20 | 22 | 1900 | 5000K | 80+ | 50,000 | - | Yes | Damp | Requires Driver |
| | G5 | 13 | 76192 | LED15T5/G/2/865 | | 20 | 22 | 1900 | 6500K | 80+ | 50,000 | - | Yes | Damp | Requires Driver |
| Remote LED Glass T5 4ft HO Tubes (Operates on Remote Driver) | | | | | | | | | | | | | | | |
| | G5 | 31 | 91973 | LED36T5/G/4/830 | | 20 | 46 | 4100 | 3000K | 80+ | 50,000 | - | Yes | Damp | Requires Driver |
| | G5 | 31 | 91976 | LED36T5/G/4/835 | | 20 | 46 | 4200 | 3500K | 80+ | 50,000 | - | Yes | Damp | Requires Driver |
| | G5 | 31 | 91977 | LED36T5/G/4/840 | | 20 | 46 | 4400 | 4000K | 80+ | 50,000 | - | Yes | Damp | Requires Driver |
| | G5 | 31 | 91997 | LED36T5/G/4/850 | | 20 | 46 | 4500 | 5000K | 80+ | 50,000 | - | Yes | Damp | Requires Driver |
| | G5 | 31 | 92006 | LED36T5/G/4/865 | | 20 | 46 | 4400 | 6500K | 80+ | 50,000 | - | Yes | Damp | Requires Driver |

Lightech Drivers - Non Dimming

| GE Product Code | Description | # of Lamps |
|-----------------|------------------|------------|
| 38970 | LED15T8/DR/UN/2L | 2 |

Lightech Drivers - Dimming

| GE Product Code | Description | # of Lamps |
|-----------------|----------------|------------|
| 38975 | LED15T8/DR/4DL | 4 |
| 38974 | LED15T8/DR/D2L | 2 |
| 92013 | LED36T/DR/4DL | 4 |
| 63126 | LED36T8/DR/D2L | 2 |

General Characteristics - Non Dimming

| GE Product Code | 38970 |
|----------------------|----------|
| Output Current (A) | 0.44*2 |
| Input Watt Range (W) | 30 |
| Input Voltage (V) | 120-277V |
| Input Frequency (Hz) | 50/60Hz |
| Efficiency (%) | > .9% |
| Output Type | DC |
| Output Volt Range | 27-33V |
| Dimmability | None |
| Ambient Temp Min | -4°F |
| Ambient Temp Max | 104°F |
| Case Temperature | 158°F |

General Characteristics - Dimming

| GE Product Code | 38974 | 63126 | 38975 | 92013 |
|----------------------|--------|----------|--------|--------|
| Output Current (A) | 0.44*2 | 1.06*2 | 0.44*4 | 1.06*4 |
| Input Watt Range (W) | 30 | 72 | 60 | 144 |
| Input Voltage (V) | | 120-277V | | |
| Input Frequency (Hz) | | 50/60Hz | | |
| Efficiency (%) | | > .9% | | |
| Output Type | | DC | | |
| Output Volt Range | | 27-33V | | |
| Dimmability | | 0-10V | | |
| Ambient Temp Min | | -4°F | | |
| Ambient Temp Max | | 104°F | | |
| Case Temperature | | 158°F | | |

Dimensions - Non Dimming

| GE Product Code | 38970 |
|-------------------------|-------|
| Weight | 1.01 |
| Casing Length (in) | 9.5 |
| Casing Width (in) | 1.3 |
| Casing Height (in) | 1.25 |
| Lead Exit Length (in) | 26 |
| Input Wire Length (in) | 36 |
| Output Wire Length (in) | 38 |

Dimensions - Dimming

| GE Product Code | 38974 | 63126 | 38975 | 92013 |
|-------------------------|-------|-------|-------|-------|
| Weight | 1.01 | 1.08 | 1.08 | 2.15 |
| Casing Length (in) | 9.5 | 9.5 | 9.5 | 16.75 |
| Casing Width (in) | 1.3 | 1.7 | 1.7 | 2.0 |
| Casing Height (in) | 1.25 | 1.25 | 1.25 | 1.25 |
| Lead Exit Length (in) | 26 | 26 | 26 | 26 |
| Input Wire Length (in) | 36 | 36 | 36 | 36 |
| Output Wire Length (in) | 42 | 42 | 42 | 42 |

ecomaginationSM



Product is compliant with material restriction requirements of RoHS



www.gelighting.com

GE and the GE Monogram are trademarks of the General Electric Company. All other trademarks are the property of their respective owners. Information provided is subject to change without notice. All values are design or typical values when measured under laboratory conditions. GE Lighting and GE Lighting Solutions, LLC are businesses of the General Electric Company. © 2016 GE.

LEDL037 (Rev. 10/11/16)